Futura

Bratt Pan















The Futura bratt pan series offers a wide range of models for versatile, efficient and ergonomic frying in every kitchen. The Futura bratt pan ensures high frying efficiency, uniform heat distribution and fast heat recovery. The Futura is quicker and more efficient than conventional bratt pans, especially when frying cold products. The temperature adjusment range is 0...250°C.

Futura pans have a strong electrical tilting as standard. The pans are available also with manual tilting and ergonomic height adjusment 800 - 950 mm. Futura pans can be supplied with food water filling by a push button.

All outer surfaces of the Hackman Futura bratt pan are made of stainless steel throughout. The frying surface is 10 mm thick steel which stores heat extremely well. Optionally available with compound surface, then the 12 mm steel base is covered with 2,5 mm stanless steel surface. Uniform surfaces and compact construction make cleaning easy.

Futura 85 and 110 pans can be either 90 or 180 mm deep which makes them very suitable for simmering and cooking of products.

Futura 110 has two separately controlled frying zones. This feature makes it possible to fry two products requiring different frying temperatures at the same time. The other way to use the frying pan is to fry a product on one zone and use the other for temporary holding.

Futura	Code	Dimensions mm	Frying area	Volume	Electric connection
Futura 60L	3755404	600x806x940	540x530	25	400V 3N~ 8,0 kW 16A
Futura 85L	3755406	850x806x940	790x530	37	400V 3N~ 12,0 kW 20A
Futura 85D	3755407	850x806x940	790x530	75	400V 3N~ 12,0 kW 20A
Futura 110L	3755408	1100x806x940	1040x530	50	400V 3N~ 16,0 kW 25A
Futura 110D	3755409	1100x806x940	1040x530	100	400V 3N~ 16.0 kW 25A

Options	Code
S/S compound surface Futura 60	3755410
S/S compound surface Futura 85	3755411
S/S compound surface Futura 100	3755412
Manual tilting	3755413
Height adjustment	3755415
Water filling	3755417











Futura 60

Futura 85 with manual tilting

Futura 110 with water filling tap and height adjustment



Aishwarya Consolidates Pvt. Ltd.,

#19, Frist Floor, 10th 'B' Main, 27th Cross, Third Block Jayanagar, BANGALORE – 560 011, INDIA Tel: +91-80-2664 1200/1/2 Fax: +91-80-2664 1204

E-mail: aishtek@vsnl.com www.aishwaryaconsolidates.com